

Product information

VELUX Roof terrace GEL + VEA/VEB/VEC



Product description

- High quality natural pinewood coated with impregnation and layers of water-based acrylic white paint or clear lacquer
- VELUX roof terrace is available as single, double or triple. Larger combinations are possible.
- Upper section: top-hung window with bottom handle for convenient operation. The window can remain open in any position up to an angle of 45°
- Lower sections, choose between:
 - VEA side-hung, outward opening sash, opens to the left
 - VEB side-hung, outward opening sash, opens to the right
 - VEC fixed sash (non-opening)
- VEA/VEB with handle on the side sash. The handle can be fitted with a lock.
- Because of structural considerations, a roof terrace can contain only one opening lower section VEA/VEB
- Triple glazing
- Ventilation flap and integrated dust and insect filter
- Maintenance-free exterior covers

Roof pitch

- Can be installed in roof pitches between 35° and 53°

Materials

- Laminated pinewood
- Glass, laminated inner glass / toughened outer glass
- Lacquered aluminium, copper or zinc

Downloads

For installation instructions, CAD drawings, 3D BIM objects, 3D GEL objects, SketchUp objects etc, please visit www.velux.co.uk

Certifications



The VELUX product factories guarantee quality systems implementation process and environmental management systems through appropriate accreditations ISO 9001 and ISO 14001

EUTR In compliance with the EU Timber Regulation (EUTR), EU regulation 995/2010

REACH We are aware of the REACH regulation and acknowledge the obligations. No products are obliged to be registered in accordance to REACH and none of our products contain any Substances of Very High Concern.

Technical values

	65G
U_w [W/m²K]	1.1
U_g [W/m²K]	0.5
R_w [dB]	35
g []	0.51
τ_v []	0.72
τ_{UV} []	0.05
Air permeability [class]	3

Thermal improvements such as lower U-value (U_w) and lower linear heat loss coefficient (φ) can be obtained with frame insulation collar and/or recessed installation.

Glazing structure

	65G
Inner glass pane	2 x 3 mm laminated float with low ε coating
Middle glass pane	3 mm heat strengthened float with low ε coating
Outer glass pane	4 mm toughened with coatings
Cavity	2 x 10 mm
Glass panes	Triple
Gas filling	Krypton

Glazing features

		65G
	Heat insulation Low energy glazing provides reduced heat loss through the window and enhanced indoor comfort.	●●●
	Solar gain In the wintertime, the heat from the sun entering through the windows is a usable solar gain.	●●
	Solar protection In warm climates and in rooms with large window areas, a sun protective coating provides a better indoor climate during summer periods. Alternatively, exterior sunscreening can be installed.	
	Sound insulation A combination of laminated glass and optimal glass thickness provides better sound insulation. Frame/sash construction and gaskets are equally important.	●●
	Security Thicker laminated inner glass pane designed to increase resistance to manual attack (burglary).	
	Safety Laminated inner glass is designed to hold the fragments together if the glass breaks. We recommend that you consider using glass units with laminated glass on the inside for windows placed above areas where people sleep, play or work.	✓
	Outside strength Toughened outer glass pane makes your glazing more resistant to hail, heavy wind and snow loads.	✓
	Delayed fading of materials Inner laminated glass protects materials behind the glass against UV radiation and therefore delays fading of the materials.	✓
	Rain noise reduction The combination of laminated glass and extra thick glass helps provide a significant, audible reduction of rainfall sound. Frame/sash construction and gaskets are equally important.	
	Easy-to-clean The easy-to-clean coating minimises the cleaning frequency of the outer glass pane and gives you a clearer view in case of rain.	✓
	Anti-dew The anti-dew coating significantly reduces the days with dew on the outer glass pane and thus gives you a clear view.	✓

● Good ●● Better ●●● Best ✓ Feature included in glazing variant

Visible features



1 Lock casing

- electro-galvanised steel
- colour: "silver"



2 Data plate upper section

- window type, size and variant code
- CE marking
- production code



3 Data plate lower, opening section



4 Data plate lower, fixed section



5 Control bar

- anodised aluminium



6 Handles

- bottom handle on upper sash in anodised aluminium
- handle on bottom sash in anodised aluminium



7 Triple glazing

- toughened outer glass
- laminated inner glass for personal safety



8 Hinges with friction

- electro-galvanised steel
- colour: "silver"



9 Barrel bolts

- plastic
- colour: grey
- steel
- colour: "silver"



10 Barrel bolt bushings

- plastic
- colour: grey/white

Cleaning and maintenance



To clean the outer pane from the inside, rotate sash and secure in cleaning position with barrel bolt.



VELUX repair and maintenance kits are available.

Exterior covers

Material	NCS standard colour	RAL nearest standard colour
Lacquered aluminium (-0-- grey)	S 7500-N	7043
Copper (-1--)	-	-
Titanium zinc (-3--)	-	-

Special colour requests, please contact enquiries@velux.co.uk

Interior finish

White paint	Impregnation and layers of water-based acrylic lacquer and paint, NCS standard colour: S 0500-N, nearest RAL standard colour: 9003.
Clear lacquer	Impregnation and layers of water-based acrylic lacquer

Special colour requests, please contact enquiries@velux.co.uk

Flashings and installation products



Flashings:

- EE- for single, twin and combi installation
- EEX – railing foundation

Available for standard and recessed installation

Installation products:

- Installation set BDX 2000 (incl BFX)
- Underfelt collar BFX 1000 incl transverse drainage gutter
- Vapour barrier collar BBX 0000
- Linings LS- (incl BBX)

Note

We reserve the right to make technical changes.


For more information on roof terrace GEL + VEA/VEB/VEC and other VELUX products, please visit www.velux.co.uk

Blinds, awnings and shutters



Interior suncreening

- Blackout blind
- Roller blind
- Pleated blind
- Flying pleated blind
- Double pleated energy blind
- Venetian blind
- Duo blackout blind



Exterior suncreening

- Awning blind
- Roller shutter



Additional accessories

- Insect roller screen

- Available in manual and mains/solar powered versions
- Available in manual and mains powered versions
- Available in manual version

The mains and solar powered versions are part of the VELUX INTEGRA® product range.